

AD-A070 882

MINNESOTA UNIV ST PAUL DEPT OF APPLIED STATISTICS

F/G 12/1

ALTERNATIVE COMPUTATIONAL METHODS FOR ESTIMATION OF LOGIT MODEL--ETC(U)

JUN 79 S E FIENBERG, M M MEYER, G W STEWART

N00014-78-C-0600

NL

UNCLASSIFIED

| OF |

AD
A070682



END
DATE
FILMED
8-79


DDC



LEVEL

II

MAC 70882




See 1473 in back.

UNIVERSITY OF MINNESOTA

**SCHOOL OF
STATISTICS**



Q **DDC**



DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

79 07 06 018

DDC FILE COPY

12 LEVEL II

ALTERNATIVE COMPUTATIONAL METHODS FOR
ESTIMATION OF LOGIT MODEL PARAMETERS

by

Stephen E. Fienberg and Michael M. Meyer

University of Minnesota

and

G.W. Stewart

University of Maryland

Technical Report No. 348

June 1979

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

DDC
RECEIVED
JUL 6 1979
B

ALTERNATIVE COMPUTATIONAL METHODS FOR ESTIMATION OF LOGIT MODEL PARAMETERS

Stephen E. Fienberg and Michael M. Meyer
School of Statistics, University of Minnesota
St. Paul, Minnesota, U.S.A.

and

G. W. Stewart
Department of Computer Science, University of Maryland
College Park, Maryland, U.S.A.

INTRODUCTION The analysis of cross-classified categorical data involves statistical problems where both the explanatory variables (or factors) and response variables are categorical. Loglinear and logit models are now widely-used in the analysis of such data (e.g. see Bishop, Fienberg, and Holland, 1975; Fienberg 1977; Haberman, 1974, 1978). Since logit models are loglinear models, the computational methods for the analysis of cross-classifications via loglinear models can also be used for analyses involving the use of logit models.

In this paper we compare three different computational approaches for maximum likelihood estimation in logit situations:

- (a) iterative proportional fitting,
- (b) iteratively reweighted least squares as implemented in GLIM (see Nelder and Wedderburn, 1972),
- (c) a variant of Newton's method, as developed by Fienberg and Stewart (1979), applied in a somewhat different form for loglinear and logit formulations.

Additional comparisons can be made with the Newton-Raphson algorithm of Haberman (1978), but they are not included here.

LOGLINEAR AND LOGIT MODELS For simplicity, consider a problem involving two explanatory variables with dimensions I and J , and a response variable of dimension K . Thus the data are counts in the form of an $I \times J \times K$ table where the totals in the $I \times J$ margin corresponding to the explanatory variables are taken as fixed. We assume that the sampling model for the counts is product-multinomial (Bishop, Fienberg, and Holland, 1975). Logit models (involving $K-1$ simultaneous logit equations) for this problem are equivalent to loglinear models that treat the three variables as if they are responses, and that include u -terms corresponding to the main effects and interaction for the explanatory variables (Fienberg, 1977, Chapter 6). Thus the iterative proportional fitting (IPF) algorithm used for loglinear models, can be used directly for logit models in this problem.

NEWTON'S METHOD Fienberg and Stewart (1979) have used a variant of Newton's method for analyzing both loglinear and logit models. Their first algorithm treats the logit model parameters as loglinear model parameters, and adjusts for the required conditioning at the end of the computation. A second algorithm proceeds by initially conditioning on the explanatory variables, and then using a somewhat different set of computations.

These algorithms involve the construction of the upper half of a $p \times p$ weighted cross-product matrix, and take full advantage of the sparseness of the $n \times p$ design matrix without actually constructing it. The algorithms proceed via Newton's method with variable step length, using a Cholesky decomposition with pivoting. Further details will be reported in the near future.

GLIM The GLIM algorithm, as developed by Nelder and his colleagues, is designed to handle the product multinomial sampling model for binary response structures, as well as other sampling models not considered here. For further details see Nelder and Wedderburn (1972). In order to handle a K-level response variable in GLIM, the user needs to treat it in an asymmetric fashion, eg. via the use of continuation ratios (see Fienberg, 1977, Chapter 6).

COMPARISONS We have summarized the qualitative aspects of the four algorithms in question in Table 1. Because the Fienberg-Stewart algorithms have opted for economy of storage over efficiency of operation, the comparisons of storage requirements between their algorithms and GLIM is misleading. In practice GLIM cannot handle as large problems as can be handled by Fienberg-Stewart algorithms.

Although we have not made direct comparisons here on speed of convergence, we note that IPF has linear convergence properties while the other algorithms have quadratic convergence. We expect that the special features in the Fienberg-Stewart algorithms should allow for convergence at a slightly faster rate than GLIM, but this should not be a serious difference between these methods. More important is the issue of numerical stability of the algorithms, where again we anticipate the superiority of the Fienberg-Stewart ones.

Whether one should use the logit or loglinear version of the Fienberg-Stewart algorithms depends on the size of the marginal array corresponding to the explanatory variables. When this margin is small some advantages may accrue to the loglinear approach.

White Section	<input checked="" type="checkbox"/>
Buff Section	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist. <input type="checkbox"/> and/or SPECIAL <input type="checkbox"/>	
A	

ACKNOWLEDGEMENT This research was supported by Office of Naval Research Contracts N00014-78-C-0151 and N00014-78-C-0600 to the University of Minnesota. Reproduction in whole or in part is permitted for any purpose of the United States Government.

REFERENCES

- Bishop, Y.M.M., Fienberg, S.E. and Holland, P.W. (1975). Discrete Multivariate Analysis: Theory and Practice. Cambridge, Mass., The MIT Press.
- Fienberg, S.E. (1977). The Analysis of Cross-classified Categorical Data. Cambridge, Mass., The MIT Press.
- Fienberg, S.E. and Stewart, G.W. (1979). "The numerical analysis of contingency tables." Unpublished manuscript.
- Haberman, S.J. (1974). The Analysis of Frequency Data. Chicago, Ill., University of Chicago Press.
- Haberman, S.J. (1978). Analysis of Qualitative Data, Volume I, Introductory Topics. New York, Academic Press.
- Nelder, J.A. and Wedderburn, R.W.M. (1972). Generalized linear models. J. Roy. Statist. Soc. A 135, 370-384.

SUMMARY Several algorithms have been proposed for the computation of maximum likelihood estimates for contingency tables. Since logit models can be treated as special versions of loglinear models, many of these same techniques can be used for logit models as well. In this paper, we compare in a qualitative fashion the relative merits of (i) the widely-used method of iterative proportional fitting, (ii) GLIM as developed by Nelder and Wedderburn, and (iii) two variants of Newton's method developed by Fienberg and Stewart.

SOMMAIRE Plusieurs algorithmes ont été proposés afin de calculer les évaluations de probabilité maximum pour les tables d'éventualité. Puisque les modèles "logit" peuvent être traités comme un cas particulier des modèles logarithmiques et linéaires, la plupart des techniques qui s'appliquent à ces derniers peuvent s'appliquer tout aussi bien aux modèles "logit". Dans cet article, nous comparons de façon qualitative les mérites relatifs des méthodes suivantes: (i) la méthode fréquemment utilisée de l'ajustement proportionnel itératif, (ii) la méthode GLIM, développée par Nelder et Wedderburn, et (iii) la méthode des deux variants de Newton, développée par Fienberg et Stewart.

Table 1: General Comparison of Methods.

Criterion	(i) Fienberg-Stewart Loglinear	(ii) Fienberg-Stewart Logit	(iii) GLIM	(iv) IPF
1. Utilizes conditioning implied by logit model	No	Yes	Yes	No
2. Handles Polytomous response structures directly	Yes	Yes	No	Yes
3. Can easily be extended to general logistic regression	No	Yes	Yes	No
4. Storage requirements	SSP matrix. ¹	SSP matrix. ²	SSP matrix. ²	Data array, plus margins. No, only by slow convergence to zero.
5. Detects non-existence of MLE's	Yes	Yes	No, only by non-convergence.	Yes
6. Handles structural zeros	Yes	Yes	No	Yes
7. Produces parameter estimates	Yes	Yes	Yes	Only for complete tables
8. Produces Covariance estimates	Yes	Yes	Yes	No
9. Detects Aliasing	Yes, via pivoted Cholesky decomposition.	Yes, via pivoted Cholesky decomposition.	Yes, via small diagonal elements in non-pivoting Gaussian elimination.	Not applicable.

¹ SSP matrix is for all loglinear parameters.

² SSP matrix is for logit parameters only.

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER Technical Report No. 348	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) ALTERNATIVE COMPUTATIONAL METHODS FOR ESTIMATION OF LOGIT MODEL PARAMETERS	5. TYPE OF REPORT & PERIOD COVERED Technical Repts	
7. AUTHOR(s) Stephen E. Fienberg, Michael M. Meyer, G.W. Stewart	6. PERFORMING ORG. REPORT NUMBER	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Department of Applied Statistics, School of Statistics, University of Minnesota, 1994 Buford Avenue, St. Paul, MN 55108	8. CONTRACT OR GRANT NUMBER(s) N00014-78-C-0600 N00014-78-C-0152	
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research 800 N. Quincy Street Arlington, VA 22217	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 12 7 P1	12. REPORT DATE June 1979	
	13. SECURITY CLASS. (of this report) Unclassified	
	13a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release: Distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Categorical data; logit models; loglinear models; iterative proportional fitting; GLIM; Newton's method.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) In this paper we compare three different computational approaches for maximum likelihood estimation in logit situations: (a) iterative proportional fitting, (b) iteratively reweighted least squares as implemented in GLIM (see Nelder and Wedderburn, 1972), (c) a variant of Newton's method, as developed by Fienberg and Stewart (1979), applied in a somewhat different form for loglinear and logit formulations.		